

**IN THE CLAIMS**

Please cancel claims 4, 12, and 20.

Please amend claims 1, 8, 9, 16, 17, 18, and 19 as indicated below.

1. (Currently Amended) A method of testing comprising:  
transmitting data via a first transmitter, wherein said data comprises:  
~~transmitting~~ a first data comprising a test pattern via a first transmitter; and  
~~transmitting~~ a second data ~~via said first transmitter~~, wherein said second data comprises a first portion of an identifier which corresponds to said first transmitter;  
receiving the first data and said second data at a first receiver;  
transmitting a first feedback data from said first receiver to said first transmitter, in response to determining said first data is correct, wherein said first feedback data is selected to be equal to said second data;  
transmitting a second feedback data from said first receiver to said first transmitter, wherein said second feedback data is not equal to said first feedback data, in response to determining said first data is not correct.
2. (Original) The method of claim 1, wherein said first data comprises a test pattern, said identifier comprises a sequence of bits, and wherein said first portion comprises a single bit of said sequence of bits.
3. (Original) The method of claim 1, wherein said first receiver determines said first data is correct in response to determining said received first data matches an expected data.
4. (Cancelled).
5. (Original) The method of claim 4, wherein said second feedback data comprises the complement of said second data.

6. (Original) The method of claim 1, further comprising assigning said identifier to said first transmitter.
7. (Original) The method of claim 6, further comprising transmitting a third data from a second transmitter, wherein said second transmitter is adjacent to said first transmitter, and wherein said third data does not equal said second data.
8. (Currently Amended) The method of claim 1, wherein said first transmitter is configured to transmit said first and second data at a first speed, and wherein said first receiver is configured to convey said first and second feedback data at a second speed, wherein said second speed is lower than said first speed.
9. (Original) A system comprising:
  - a first transmitter, wherein said first transmitter is configured to transmit data,  
wherein said data comprises:
    - ~~transmit~~ a first data comprising a test pattern; and
    - ~~transmit~~ a second data, wherein said second data comprises a first portion of an identifier which corresponds to said first transmitter;
  - a first receiver coupled to said first transmitter, wherein said first receiver is configured to:
    - receive the first data and second data;
    - determine whether said received first data is correct;
    - transmit a first feedback data to said first transmitter, in response to determining said first data is correct, wherein said first feedback data is selected to be equal to said second data; and
    - transmit a second feedback data to said first transmitter, wherein said second feedback data is not equal to said first feedback data, in response to determining said first data is not correct.

10. (Original) The system of claim 9, wherein each of said first data and said identifier comprise a sequence of bits, and wherein said first portion comprises a single bit of said sequence of bits.
11. (Original) The system of claim 9, wherein said first receiver is configured to determine said first data is correct responsive to determining said received first data matches an expected data.
12. (Cancelled).
13. (Original) The system of claim 12, wherein said second feedback data comprises the complement of said second data.
14. (Original) The system of claim 13, further comprising a second transmitter adjacent to said first transmitter, wherein said second transmitter is configured to transmit a third data, wherein said third data does not equal said first data.
15. (Original) The system of claim 9, wherein said first transmitter is configured to transmit said first and second data at a first speed, and wherein said first receiver is configured to convey said first and second feedback data at a second speed, wherein said second speed is lower than said first speed.
16. (Original) A system comprising:  
  
a first transmitter configured to transmit data, wherein said data comprises:  
transmit a first data comprising a test pattern; and  
~~transmit~~ a second data, wherein said second data comprises a first portion of an identifier which corresponds to said first transmitter;

a first receiver coupled to said first transmitter, wherein said first receiver is configured to:  
receive the first data and second data;  
determine whether said received second data is correct;  
transmit a first feedback data to said first transmitter, in response to determining said first data is correct; and  
transmit a second feedback data to said first transmitter, wherein said second feedback data is not equal to said first feedback data and is selected to be equal to the complement of said second data, in response to determining said first data is not correct.

17. (Currently Amended) The system of claim [15] 16, wherein each of said first data and said identifier comprise a sequence of bits, and wherein said first portion comprises a single bit of said sequence of bits.
18. (Currently Amended) The system of claim [15] 16, wherein said first receiver is configured to determine said first data is correct responsive to determining said received first data matches an expected data.
19. (Currently Amended) The system of claim [15] 16, wherein said first feedback data is equal to said second data.
20. (Cancelled).
21. (Original) The system of claim 19, further comprising a second transmitter adjacent to said first transmitter, wherein said second transmitter is configured to transmit a third data, wherein said third data does not equal said first data.